

STARK PCE UNIT COOLERS - TECHNICAL SPECIFICATION

(2023-03)

7MM FIN SPACING (ELECTRIC DEFROST)

Model	NOMINAL CAPACITY R404A				FAN DATA						Coil Heater (Watts)	Drain Pan Heater (Watts)
	EUROVENT SC3 (7KTD)		EUROVENT SC2 (8KTD)		No. of Fans	V/Ph/Hz	Watts	Amps	Air Flow (m³/hr)	Air Throw (m)		
	KW	BTU/HR	KW	BTU/HR								
PCE-3/15/401	3.06	10,441	3.92	13,375	400 x 1	400/3/50	180	0.5	3700	10	1000x1	1000
PCE-3/15/302	3.06	10,441	3.92	13,375	300 x 2	230/1/50	90x2	0.42x2	1750x2	8	1000x1	1000
PCE-4.4/22/401	4.40	15,013	5.72	19,517	400 x 1	400/3/50	180	0.5	3700	10	1200x2	1200
PCE-4.4/22/352	4.40	15,013	5.72	19,517	350 x 2	230/1/50	135x2	0.6x2	2700x2	8	1200x2	1200
PCE-6/30/501	6.10	20,813	7.93	27,057	500 x 1	400/3/50	420	0.9	6500	12	1300x2	1300
PCE-6/30/402	6.10	20,813	7.93	27,057	400 x 2	400/3/50	180x2	0.5x2	3700x2	10	1300x2	1300
PCE-8/40/501	8.16	27,842	10.60	36,167	500 x 1	400/3/50	420	0.9	6500	12	1500x2	1500
PCE-8/40/402	8.16	27,842	10.60	36,167	400 x 2	400/3/50	180x2	0.5x2	3700x2	10	1500x2	1500
PCE-12/60/502	12.12	41,353	15.90	54,251	500 x 2	400/3/50	420x2	0.9x2	6500x2	12	1300x5	1300
PCE-16/80/502	16.25	55,445	21.40	73,017	500 x 2	400/3/50	420x2	0.9x2	6500x2	12	1700x5	1700
PCE-18/100/503	20.20	68,922	26.90	91,783	500 x 3	400/3/50	420x3	0.9x3	6500x3	12	2000x5	2000
PCE-24/120/503	24.20	82,570	32.20	109,866	500 x 3	400/3/50	420x3	0.9x3	6500x3	12	2200x5	2200
PCE-28/140/504	28.30	96,560	37.60	128,291	500 x 4	400/3/50	420x4	0.9x4	6500x4	12	2400x5	2400
PCE-32/160/504	32.30	110,208	42.90	146,375	500 x 4	400/3/50	420x4	0.9x4	6500x4	12	2600x5	2600
PCE-40/200/504	40.20	137,162	52.30	178,448	500 x 4	400/3/50	420x4	0.9x4	6500x4	12	2600x5	2600

EUROVENT SC2: 0°C Air Inlet & -8°C Evaporating Temperature.

EUROVENT SC3: -18°C Air Inlet & -25°C Evaporating Temperature.